

For more information visit www.hagerco.com



3573 - Corridor/Dormitory (F90)

Applications Standard Duty Commercial











PRODUCT SPECIFICATIONS

Backsets:

2-3/4" (70mm) 2-3/8" (60mm) 3-3/4" (94mm) 5" (128mm)

Certifications:

ADA Compliant ANSI A117.1 Accessibility Code UL/cUL Listed for all functions up to 3 hours "A" label single doors UL10C Positive Pressure Rated BHMA Certified ANSI A156.2, Series 4000, Grade 2 ANSI A250.13 Severe Windstorm Compliant (Leversets Only) Miami Dade County, FL NOA #17-1226.23

Cylinders/Cores:

Keyed Different - standard
Cylinder drilled 6 pin, Keyed 5 pin - standard
Other Keying options, including 6 pin keyed, available from factory
Zero bit cylinders will be 6 pin keyed
SFIC uncombinated or combinated, brass 6 pin or 7 pin cores sold separately

Door Thickness:

1-3/8" - 2" (35 mm - 51 mm)

Exposed Trim:

Wrought brass, bronze, and stainless steel Lever is zinc based, plated to match BHMA symbols

Finishes:

US3, US4, US10, US10B, US26 and US26D Anti-Microbial coating (US26D finish Only)

Functions:

Corridor/Dormitory (F90)

Kevway

Schlage C - Standard, other keyways optional

Latchbolt Type:

1/2" (13 mm) throw, stainless steel
1-1/8" x 2-1/4" (29 mm x 57 mm) faceplate for 2-3/4" (70 mm) backset

1" \times 2-1/4" (25 mm \times 57 mm) faceplate for 2-3/8" (60 mm) backset Deadlocking latchbolt prevents manipulation when door is closed

Lever Options:

Archer, August and Withnell

Lock Chassis:

Heavy gauge steel, zinc dichromated for corrosion resistance. Thruposts are removable. Failure to install thru-posts and screws voids BHMA certification, UL rating, and warranty

Notes

No exposed mounting screws Non-handed

Options:

Lead Lining Tactile Warning Split Finish

Rose Diameter:

3-11/32" (85 mm)

Strikes

1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike Optional strikes available

Warranty:

Lifetime