

9' Mod-SM-Long-9 - Specification Sheet

Features

- Dimmable LED task lighting
- Energy efficient LED lighting 5000K
- 6360 Lumens
- CRI 90+
- Integrated Defogger

Construction

- Quality polished edge mirror
- Single phase wire installation, silver backed, copper free
- Construction for surface mounting
- Includes installation hardware



Codes/Standards Applicable

- Conforms to UL Std. 962
- Cert. to CSA Std. C22.2 No.250.0-08
- ETL Intertek 5004931

Electrical System

Mod3636L:

- 120Vac, 60Hz, 55.5W
- Electric Current: 0.46A
- Wattage: 55.5W

Mod3636Center:

- 120Vac, 60Hz, 46.6W
- Electric Current: 0.38A
- Wattage: 46.6W

Mod3636R:

- 120Vac, 60Hz, 55.5W
- Electric Current: 0.46A
- Wattage: 55.5W

Model

- 9' Mod-SM-Long-9
- Combo of:
 - MODULAR 3636 Left LED Mirror
 - MODULAR 3636 Center LED Mirror
 - MODULAR 3636 Right LED Mirror

9' Mod-SM-Long-9 - Specification Sheet

Dimensions

Mod3636L:

- Height: 36"
- Width: 36"
- Depth: 1-9/16"


Mod3636Center:

- Height: 36"
- Width: 36"
- Depth: 1-9/16"


Mod3636R:

- Height: 36"
- Width: 36"
- Depth: 1-9/16"


FRONT



BACK



SIDE



FRONT, BACK & SIDE

MODEL	A	B	C	D	E	F
9' Mod-SM-Long-9	108	36	17-7/8	17-7/8	1-3/8	3/16