

## **TAFT**

**794**(

**Widespread Lavatory Faucet** 

### **Features**

- Solid brass construction
- · Brass valve bodies
- Quarter-turn washerless ceramic disc valve cartridges
- Spout assembly with integral supply hoses
- Push Pop-Up drain with tailpiece
- 2.23" (5.7 cm) spout height at outlet
- 6.01" (15.3 cm) spout reach (c-c)
- For 8" (20.3 cm) centers Maximum 20" (50.8 cm)
- ADA Compliant
- 1.2 GPM (4.5 LPM) Max

### **Codes / Standards Compliance**

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAMPO/cUPC
- NSF/ANSI/CAN
- IPC
- ADA & ICC/ANSI A117.1
- Energy Policy Act of 1992
- EPA WaterSense
- California Energy Commission
- All applicable US Federal and State material regulations



### **Colors / Finishes**

10B: Oil Rubbed Bronze15: Polished Nickel15S: Satin Nickel - PVD26: Polished Chrome

• Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model		
Model	Description	Colors   Finishes
2940	Widespread Lavatory Faucet	10B 15 15S 26 Other

### Product Specification: Add size designator and "Color / Finish" suffix to Model number, below.

The two-handle Widespread Lavatory Faucet shall be made of solid brass construction. Faucet shall incorporate a spout assembly with integral supply hoses and feature brass valve bodies with quarter-turn washerless ceramic disc valve cartridges. Faucet shall have a 1.2 gallon (4.5 liter) per minute maximum flow rate. Product shall be for 8" (20.3 cm) centers - Maximum 20" (50.8 cm). Product shall incorporate a 2.23" (5.7 cm) spout height at outlet and a 6.01" (15.3 cm) spout reach (c-c). Faucet shall include a Push Pop-Up drain with tailpiece and incorporate lever handles. Widespread Lavatory Faucet shall be Newport Brass Model 2940/\_\_\_\_.

# 2940

Product Dimensions are provided for reference only. For specific product installation guidelines, please reference the Installation Instructions of the product being installed.

