

Model 334 — Recessed **BradEX**® (Waste container projects 8¾")
Model 334-10 — Semi-Recessed (recesses 2"; projects 10¾")
Model 334-11 — Surface-Mounted (projects 12¾")

Standard Series — Satin Finish

✓ 18-Gallon Capacity

Product Materials

FLANGE: 22-gauge stainless steel with exposed surfaces in architectural satin finish. One piece seamless construction, 1" wide with ¼" return.

CABINET: Heavy gauge stainless steel. All welded construction.

WASTE CONTAINER: 22-gauge stainless steel. All welded construction. Secured to cabinet with tumbler lock keyed like other Bradley units.

LINER: (Optional) Heavy-duty stitched vinyl-coated nylon.

HINGED COVER: (Optional) 22-gauge stainless steel with exposed surfaces in architectural satin finish. Heavy-duty stainless steel piano hinge.

PUSH FLAP DOOR: (Optional) Fabricated of 22-gauge stainless steel with exposed surfaces in architectural satin finish. Heavy-duty stainless steel piano hinge. Self-closing flap door is embossed PUSH.

Capacity

18 gal. (2.5 cu. ft.)

Operation

Receptacle removable for servicing by unlocking waste container.

Installation

Verify all rough-in dimensions prior to installation. Recessed unit requires rough wall opening 15-5/8"W x 29-1/8"H x 4"D. Secure to framing with mounting screws (included) at holes provided. Shim at screw points as required.

Guide Specification

Recessed waste receptacle shall be fabricated of heavy gauge stainless steel with seamless exposed surfaces in satin finish. Removable 18-gallon stainless steel waste receptacle. Heavy-duty vinyl liner is optional. Receptacle secured to cabinet with tumbler lock.

Overall dimensions: 17-1/8" W x 30-5/8" H x 12-3/4" D.



ADA Compliant

- Consult local and national accessibility codes for proper installation quidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.

Optional Features

Feature


Vinyl Liner Part #P11-001

Orders composed of products indicated as **BradeX** will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.

Page 1 of 2 6/19/2023
This information is subject to change without notice.
Bradley_WasteReceptacle_334_10_11

View Latest Version





| Dim. "A" Key Surface: | For Dim. "A" | Top of Rough Wall Opening | Bottom of Rough Wall Opening |
|--|---|---------------------------|------------------------------|
| Waste receptacle top lip to finished floor | 36" (914) | 41¾" (1060) | 125/8" (321) |
| | 32" (813) | 37¾" (959) | 85%" (219) |
| | 28" (711) | 33¾" (857) | 45%" (117) |
| Rough wall opening: | | | |
| Surface Mount: | No rough opening, see overall dimensions | | |
| Recessed: | 15%" (397) Wide x 291/s" (740) High x 4" (102) Deep | | |
| Semi-Recessed: | 15%" (397) Wide x 291%" (740) High x 2" (51) Deep | | |

Orders composed of products indicated as **BradleX**® will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.

Page 2 of 2 6/19/2023
This information is subject to change without notice.
Bradley_WasteReceptacle_334_10_11

View Latest Version

© 2023 Bradley
P.O. Box 309, Menomonee Falls, WI 53052-0309
800 BRADLEY (800 272 3539) +1 262 251 6000
bradleycorp.com