

**Model 6322**

- Pump-Type Valve
- 2½" Spout, 4¾" Shank
- ADA Compliant

**Product Materials**

**PLUNGER AND SPOUT:** stainless steel. Takes less than 5 lbs. of force to activate plunger.  
**ESCUTCHEON:** heavy chrome-plated brass.  
**SHANK:** molded ABS plastic.  
**VALVE CYLINDER:** molded clear ABS plastic.  
**VALVE COMPONENTS:** Celcon, Buna-N rubber or stainless steel.  
**PLASTIC GLOBE:** translucent polyethylene.

**Operation**

Depress piston for measured amount of liquid soap. Fills from top by unlocking and withdrawing piston and spout assembly using special wrench provided. The 6322 will dispense vegetable or coconut oil liquid soaps, synthetic detergents, and antiseptic solutions in a liquid form. Spout is fixed. Less than 5 lbs. force to activate.

- Bradley liquid soap valves operate best with any vegetable oil or coconut oil hand soap having a 10–15% soap concentration.

**Installation**

Verify all rough-in dimensions prior to installation. Mount dispenser in 1" diameter hole in lavatory or countertop. Include dispenser mounting hole location in lavatory specifications or mount in unused faucet hole. Shank will accommodate a max. 3½" mounting thickness and can be cut in the field.

**Optional Features**

Feature	Suffix
<input type="checkbox"/> Metal globe (stainless steel) 16 oz.	-67
<input type="checkbox"/> Plastic globe 32 oz.	-68

**Guide Specification**

Lavatory-mounted liquid soap dispenser manufactured of stainless steel, chrome-plated brass and molded ABS plastic. Buna-N O-ring seals and duckbills. Valve dispenses measured amount of vegetable or coconut oil, liquid soap, synthetic detergents, or antiseptic solutions. Servicing is facilitated by use of special wrench. Requires less than 5 lbs. of force to activate.

**ADA Compliant**

- Consult local and national accessibility codes for proper installation guidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.

The diagram shows a top-down view of the soap dispenser with the following dimensions: Spout length is 2½" (64mm). The escutcheon has a diameter of 2" (51mm) and a thickness of 2¾" (70mm). The mounting hole diameter is 13/16" (21mm) and the maximum mounting thickness is 3½". The globe height is labeled 'A"' and the globe diameter is labeled 'B"'. An ADA compliant icon is located in the top right corner of the diagram area.

DIMENSIONS			
Model	A	B	Capacity
6322	7½" (181mm)	2½" (64mm)	16 oz.
6322-67	5" (127mm)	2¾" (70mm)	16 oz.
6322-68	8¼" (209mm)	3¼" (86mm)	32 oz.