



Base Model	Description	Base Price
902000026D41	Auxiliary Lock with Thumbturn, 1" (25 mm) Deadbolt, Fits 13/8"–11/2" (35 mm–38 mm) thick	\$174.00

## **Choose One Option from This Category**

Model Options	Description	Price
02	1" (25 mm) Deadbolt Latch, $1\frac{3}{8}$ " – $1\frac{1}{2}$ " (35 mm – 38 mm) thick	No Charge
04	1" (25 mm) Deadbolt Latch,1¾"–2½" (44 mm–54 mm) thick	No Charge
06	1" (25 mm) Deadbolt Latch,1¾"-1½" (35 mm-38 mm) thick, key override	Add \$58.00
10	1" (25 mm) Deadbolt Latch,1¾"-21%" (44 mm-54 mm) thick, key override	Add \$58.00
17	5%" (16 mm) Deadlocking Spring Latch, flat front, 13%"–11½" (35 mm–38 mm) thick, latch holdback	Add \$25.00
19	5/8" (16 mm) Deadlocking Spring Latch, flat front, 13/4"–21/8"(44 mm–54 mm) thick, latch holdback	Add \$25.00
20	5%" (16 mm) Deadlocking Spring Latch, flat front, 13%"–11½" (35 mm–38 mm) thick, no latch holdback	Add \$25.00
22	5/8" (16 mm) Deadlocking Spring Latch, flat front, 13/4"–21/8" (44 mm–54 mm) thick, no latch holdback	Add \$25.00
27+	5/8" (16 mm) Deadlocking Spring Latch, flat front, 13/8"–11/2" (35 mm–38 mm) thick	Add \$114.00
29+	5/8" (16 mm) Deadlocking Spring Latch, flat front, 13/4"–21/8" (44 mm–54 mm) thick	Add \$114.00
35*	5/8" (16 mm) Deadlocking Spring Latch, flat front, 13/8"–11/2" (35 mm–38 mm) thick, latch holdback, key override	Add \$82.00
38*	5/8" (16 mm) Deadlocking Spring Latch, flat front, 13/4"–21/8" (44 mm–54 mm) thick, latch holdback, key override	Add \$82.00

<sup>\*</sup> Key override orders will consist of all locks on the order being keyed alike, unless there is a specific key cut called out or the locks on the order are requested to be keyed differently



## Choose up to Four Options - Insert 0 if Less than Four Options are required.

Options	Description	Price
1	Substitutes a surface-mounted strike box for metal door frames in place of the standard strike box (part number 74464) (see 900 Series Accessories—Adapter Kit)	Add \$5.00
2	Deletes the key cylinder from key override models. Recessed escutcheon recommended for standard rim cylinder installation. Rim cylinder tailpiece must be reduced in width to accommodate the tail receptacle. Specify the position of the cylinder tailpiece (vertical or horizontal) to mate with the standard size rim cylinder (not supplied).	Less \$21.00
3	Substitutes a 2½" (64 mm) lever in place of the standard inside thumbturn (part number 74437) (cannot be used with option 5)	Add \$32.00
4*	Master Keyed (key override models)	Add \$12.00
5	Adds the panic bar release kit to a spring latch model (part number 74438) (cannot be used with option 3)	Add \$34.00
6	Deletes latch holdback (935 and 938 models)	No Charge
7	Deletes the key cylinder from key override models and changes gear plate to a 100 Series. Recessed escutcheon recommended for standard rim cylinder installation. The rim cylinder tailpiece must be reduced in width to accommodate the tail receptacle. Specify the position of the cylinder tailpiece (vertical or horizontal) to mate with the standard size rim cylinder (not supplied).	Less \$21.00
8	Changes gear plate to accept a horizontal tailpiece	No Charge

Finish Options	Description	Price
26D	Satin Chrome (Powder Paint)	No Charge
04++	Satin Brass (Powder Paint)	No Charge

## Notes

<sup>\*</sup>D.O.D. Compliant

<sup>\*\* 04</sup> Finish not available on Model 927/929

<sup>\*</sup> Key override orders will consist of all locks on the order being keyed alike, unless there is a specific key cut called out or the locks on the order are requested to be keyed differently.