

MORTISE HANDLESETS ANSI/BHMA Grade 1



SPECIFICATIONS

Door Thickness	1-3/4 ["] (44mm) standard Thick Door Kits available
Backset	MT620: 2-1/2"(63.5mm) Standard MT720: 2-3/4"(70mm) Optional
Lockcase	Field reversible without disassembly
Handing	Handing specification required
Center Distance	Lever to Cylinder 3-5/8"(92mm) Lever to Thumbturn 2-7/16" (62mm)
Cylinder & Keys	Keying service available 6-pin Schlage C Keyway Cylinder with 2 keys
Standard Cylinder Size for 1-3/4" Door	NY/MH Trim: 1-1/4" Cylinder ME/BW Trim: 1-1/8" Cylinder

FUNCTION



Key from outside locks and unlocks

Thumb-piece from outside retracts latchbolt. Thumbturn from inside locks

Inside lever is always unlocked allowing

Toggle always in locked position unless set to unlock manually.

Locking deadbolt by thumbturn or key resets toggle to locked position.

Entry Dummy (MTEDP)

NY/MH/ME/BW trim with dummy cylinder outside, dummy plate escutcheons inside.

Description	Part Number	Standard Finish Options	
Mortise Handlesets	NY Trim BW Trim	32D Satin Stainless Steel 32 Bright Stainless Steel 10B Oil Rubbed Bronze 19G Graphite Black PVD4 Satin Brass	
Mortise Handlesets MH Trim ME Trim		SP Split Finish 32D Satin Stainless Steel 32 Bright Stainless Steel 10B Oil Rubbed Bronze SP Split Finish	

For additional finish options not listed, contact Sales Department for MOQ and lead times




LEVER DESIGNS AND FINISHES (FOR INSIDE HANDLESET)




www.inoxproducts.com

MORTISE LOCKCASE & DIMENSIONS

ANSI/BHMA Grade 1



- 1. 1" throw, heavy duty stainless steel deadbolt
- 2. Guarded, two-piece stainless steel 3/4" latch bolt projection with mechanical anti-friction tongue
- 3. Auxiliary latch deadlocks latch bolt when door is closed, providing extra security
- 4. Field reversible: latch direction can be easily reversed without opening lock case
- 5. When toggle switch is locked, outside lever is inoperative; when toggle switch is unlocked, outside lever is operative



MT620 Mortise Lock Dimensions

MT720 Mortise Lock Dimensions



MT MORTISE LOCKCASE

For all Mortise Handles ets only w/faceplate, strike and dustbox (less cylinder)

Illustration	Backset	Function	Item Code
	2-1/2″	Entry w/ Toggle	MT620- 32D/32/10B
	2-3/4"	Entry w/ Toggle	MT720- 32D/32/10B

* MT Lock built-in toggle buttons are set to be locked by default, which deactivates the outside thumb-piece. This allows door to be kept locked even without using key or thumbturn to engage deadbolt. Toggle can be manually set to unlocked position, in which case the outside thumbpiece will engage the latch bolt and act as a passage latch until the toggle is reset to locked position, either manually or set automatically by using thumbturn or key.


MT MORTISE FACEPLATE AND STRIKE

Illustration	Function	Item Code
<u>•</u>	MT Mortise Faceplate	MT-FSP20- 32D/32/10B
	MT Mortise Strike	LSR-MT01- 32D/32/10B
	MT Mortise Strike Dust Box	LSR-DBX-MT

KEYING SERVICES

Description	Item No.
Service: Key Cut including Key Blank	SV-KYCT
Service: Keyed Alike (KA)	SV-KA
Service: Keyed to Specific Code	SV-KS
Service: Master Keying	SV-MK
Service: Grand Master Keying with 2 or more Master groups.	SV-GMK
Service: Construction Master Keying Service	SV-CMK

MORTISE CYLINDERS AND KEYS



Schlage C Keyway, 6 Pin, with Clover Cam, 2 Keys. Standard Keyed Differ (KD). Other Keying Service available. Standard Cylinder Size for 1-3/4" Door: NY and MH Trim: 1-1/4" Mortise Cylinder ME and BW Trim: 1-1/8" Mortise Cylinder Please refer to Price Book for details of Thick Door Kits (TDK)

Product Illustration	Description	Item No.
	1-1/8" Mortise cylinder with MT cam	CMB1186 CAM04-MT
	1-1/4" Mortise cylinder with MT cam	CMB1146 CAM04-MT
	1-3/8" Mortise cylinder with MT cam	CMB1386 CAM04-MT
	1-1/2" Mortise cylinder with MT cam	CMB1126 CAM04-MT
	1-5/8" Mortise cylinder with MT cam	CMB1586 CAM04-MT
	1-3/4" Mortise cylinder with MT cam	CMB1346 CAM04-MT
	Key blanks Schlage C Keyway 6 pin for Mortise Cylinder	LSK01-6SC- NP

