

# 1250

## Single Acting Square Corner

### Application:

- For maximum versatility use all spring hinges or a combination of spring hinges and ball bearing hinges. Do not use plain bearing hinges.
- Full spring tension may not be required on all hinges
- Strong wind conditions, drafts, carpeting drag, twisted/misaligned frames, or weatherstripping on doors may require additional spring hinges

### Notes:

Available in hospital tip (voids UL)



## PRODUCT SPECIFICATIONS

### MATERIAL:

- Steel with Steel components ANSI K81071F

### FINISHES:

- USP, US3, US4, US10, US10A, US10B, US26D

### NOTES:

- Hager does not recommend using spring hinges on doors over 70"

## PRODUCT SIZE OPTIONS

HINGE SIZE (INCHES)	HINGE SIZE (MM)	GAUGE OF METAL	HOLE COUNT	SCREW SIZE (MACHINE)	SCREW SIZE (WOOD)
3 1/2 x 3 1/2	89 x 89	0.134	6	1/2 x 10-24	1 x 9
4 x 4	102 x 102	0.134	8	1/2 x 12-24	1 1/4 x 12
4 1/2 x 4	114 x 102	0.134	8	1/2 x 12-24	1 1/4 x 12
4 1/2 x 4 1/2	114 x 114	0.134	8	1/2 x 12-24	1 1/4 x 12

SERIES 1 3/4" (45MM) DOOR	SIZE	RCM MAX DOOR WT. (LBS)	SPRING HINGE	BALL BEARING HINGE
1150	4 1/2 x 4 & 4 1/2 x 4 1/2	70	1	2
1150	4 1/2 x 4 & 4 1/2 x 4 1/2	115	2	1
1150	4 1/2 x 4 & 4 1/2 x 4 1/2	150	3	---
1250	4 1/2 x 4 & 4 1/2 x 4 1/2	70	1	2
1250	4 1/2 x 4 & 4 1/2 x 4 1/2	115	2	1
1250	4 1/2 x 4 & 4 1/2 x 4 1/2	150	3	---
1256	4 1/2 x 4 1/2	115	2	1
1255	4 1/2 x 4 1/2	115	2	1