

# 1251

# Single Acting 1/4" Radius

# Application:

- For maximum versatility, use all spring hinges or a combination of spring and ball bearing hinges. Do not use plain bearing hinges.
- Strong wind conditions, drafts, carpeting drag, twisted/misaligned frams, or weatherstripping on doors may require additional spring hinges





# **PRODUCT SPECIFICATIONS**

#### MATERIAL:

- Steel with Steel components ANSI K81071F

#### FINISHES:

- USP, US3, US4, US10, US10A, US10B, US26D

#### NOTES:

- Hager does not recommend using spring hinges on doors over 7'0"

# **PRODUCT SIZE OPTIONS**

HINGE SIZE (INCHES)	HINGE SIZE (MM)	GAUGE OF METAL	HOLE COUNT	SCREW SIZE (MACHINE)	SCREW SIZE (WOOD)
3 1/2 x 3 1/2	89 x 89	0.134	6	1/2 x 10-24	1 x 9
4 x 4	102 x 102	0.134	8	1/2 x 12-24	11/4 x 12
4 1/2 x 4	114 x 102	0.134	8	1/2 x 12-24	11/4 x 12
4 1/2 x 4 1/2	114 x 114	0.134	8	1/2 x 12-24	11/4 x 12