

## 282D

### Product Information

---

- Notes:**
- Sold in increments of 2
  - 3-hour fire rating for metal doors up to 4 feet wide by 10 feet tall
  - 282S strike plate bag and 282P bolt head available
  - For use on hollow metal/fire rated doors
  - 282R optional rod length available: 18" (457 mm) , 25" (635 mm), and 30" (762 mm) (bolt head not included) - no charge
  - Non-handed
  - Bolt head rods are adjustable

Manual Flush Bolt



### Product Specifications

---

- Certifications:** - Meets ANSI 156.16 for L14251
- Face Plate:** - 1" x 6-3/4" (25 mm x 172 mm)
- Flattened Round Bolt Head:** - 1/2" (13 mm) square
- Bolt Throw:** - 3/4" (19 mm)
- Standard Rod Length:** - 12" (305 mm) (from center of face to corner of door)
- Bolt Backset:** - 3/4" (19 mm)
- Guide Plate:** - 1" x 2" (25 mm x 51 mm)
- Mortise strike:** - 15/16" x 2-1/4" (24 mm x 57 mm)
- Optional Rod Length:**
- 18" (457 mm)
  - 25" (636 mm)
  - 30" (762 mm)
  - Specify 282R
- Materials:** - Brass faceplate with steel components
- Finishes:** - US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D
- Fasteners:**
- Eight (8) #8 x 3/4" combo screws
  - Eight (8) #8 x 1-1/2" combo screws