

2925

Electric Door Strike

Description:

- Centerline Electric Strike
- Designed for use with cylindrical and mortise lockset with up to 5/8" (15mm) throw latch bolts with 1/8" door gap
- Compact low profile design with internally mounted solenoid and factory-supplied mounting tabs



PRODUCT SPECIFICATIONS

FEATURES:

- Low profile - 1.25" (32 mm) backset
- Reversible Fail Safe - Fail Secure
- Latch status output standard
- Quick and easy installation where jamb space is limited
- For 1/2" (13 mm) latch or 5/8" (16 mm) latch with 1/8" (3 mm) door gap
- Latch status output, 3 amp - SPDT
- Non-handed, reversible
- All stainless steel parts with durable diecast body for corrosion resistance
- 630 stainless steel standard finish

FINISH:

- US32D

INPUT:

- 200/100 mA @ 12/24 VDC

LATCH STATUS:

- SPDT, 3 amp @ 30 VDC

DIMENSIONS:

- 1-1/4" (w) x 4-7/8" (h) x 1-1/4" (d)
- 32 (w) x 124 (h) x 32 (d) mm

OPTIONS:

- BUZZ - buzzer 12/24 VDC (2-679-0028)
- RECT - rectifier for AC operation (2-679-0029)