

2928

Multi-Application Electric Strike



Description:

- Centerline electric strike
- Designed for use with cylindrical and mortise lock sets with up to 3/4" (19 mm) throw latch bolt with 1/8" door gap
- Compact low profile design with internally mounted solenoid and factory-supplied mounting tabs
- Fewer moving parts for maximum life
- Ideal for high traffic applications
- ANSI A156.31, Grade 2

PRODUCT SPECIFICATIONS

FEATURES:

- Low profile - 1-3/16" (30 mm) deep
- Field selectable Fail Secure or Fail Safe
- Field selectable voltage, 12/24V AC/DC
- For 5/8" (16 mm) latch or 3/4" (19 mm) latch with 1/8" (3 mm) door gap
- 1/4" (6 mm) horizontal alignment adjustment
- Non-handed
- All stainless steel parts with durable diecast body for corrosion resistance
- Latch position status and keeper locked/unlocked status standard
- Keeper open/closed and status optional
- 1/4" (6 mm) horizontal alignment adjustment
- Plug-in pig tail connectors

MODELS:

- 2928-SC - 4-7/8" (124 mm) x 1-1/4" (32 mm) square corner faceplate
- 2928-RC - 4-7/8" (124 mm) x 1-1/4" (32 mm) radius corner faceplate
- 2928-6R - 6-7/8" (175 mm) x 1-1/4" (32 mm) radius corner faceplate
- 2928-7R - 7-15/16" (202 mm) x 1-7/16" (36 mm) radius corner faceplate

FINISHES:

- US32D stainless steel (standard with 2928-SC)
- ALM aluminum (standard with 2928-RC, 2928-6R, and 2928-7R)

DUAL VOLTAGE COIL:

- 200/100 mA @ 12/24V DC
- 140/70 mA @ 12/24V AC

STATUS:

- Latch position status (standard): SPDT, Dry 3Amp @ 30VDC
- Keeper locked/unlocked status (standard): SPDT, Dry 3Amp @ 30VDC
- Keeper open/closed status (optional): SPDT, Dry 3Amp @ 30VDC

DIMENSIONS:

- 1-1/4" (w) x 4-7/8" (h) x 1-3/16" (d)
- 32 (w) x 124 (h) x 30 (d) mm

OPTIONS:

- KOC - keeper open/closed status
- BUZZ - buzzer 12/24 VDC (2-679-0028)