

Product Information

- Notes:**
- Thermal lock automatically locks inactive door under high fire/heat conditions
 - 280X dust proof strikes are recommended for use with these sets
 - 3-hour fire rating for metal doors up to 4 feet wide by 9 feet tall
 - Consists of one 292S and one 293S for two point latching
 - Inactive door remains latched until the active door is opened, releasing the automatic bottom bolt - Top bolt can be manually released by pressing plunger - Inactive door will relatch automatically when closed
 - Non-handed
 - Bolt head rods are adjustable

Self-Latching Flush Bolt Set
For Inactive Metal Doors



Product Specifications

- Faceplate:** - 1" x 6-3/4" (25 mm x 172 mm)
- Flattened Square Bolt Head:** - 1/2" (13 mm)
- Bolt Throw:** - 3/4" (19 mm)
- Materials:** - Stainless steel brass with steel components
- Finishes:** - US3, US4, US10, US10B, US15, US32, US32D
- Fasteners:** - Eight (8) #8 x 1" combination screws
- T-Strike:** - 1-1/8" x 2-3/4" (28 mm x 70 mm)
- Bolt Backset:** - 3/4" (19 mm)
- Certifications:**
- A, B, C, D, and E Label
 - ANSIA156.3 Type #27

