

Product Information

- Notes:**
- One set consists of One 291S and One 294S for two point latching
 - Thermal lock automatically locks inactive door under high fire/heat conditions
 - 280X dust proof strikes are recommended for use with these sets
 - 1-1/2 hour fire rating for wood doors up to 4 feet wide by 9 feet tall
 - Inactive door remains latched until the active door is opened, releasing the automatic bottom bolt - Top bolt can be manually released - Inactive door will relatch automatically when closed
 - Non-handed
 - Bolt head rods are adjustable

Self Latching Flush Bolt Set
For Inactive Wood Covered Composite Doors



Product Specifications

- Faceplate:** - 1" x 8-1/2" (25 mm x 216 mm)
- Flattened Square Bolt Head:** - 1/2" (13 mm)
- Bolt Throw:** - 3/4" (19 mm)
- Materials:** - Stainless steel and brass with steel components
- Finishes:** - US3, US4, US10, US10B, US15, US32, US32D
- Fasteners:**
- Three (3) #10 x 1" SMS
 - Four (4) #8 x 1" combo screws
 - Two (2) plastic anchors
- T-Strike:** - 1-1/8" x 2-3/4" (28 mm x 70 mm)
- Bolt Backset:** - 3/4" (19 mm)
- Certifications:**
- B, C, D, and E Label
 - ANSI A156.3 Type #27

