

**Product Information**

---

- Notes:**
- Fire bolt is activated at 230° F projecting into active door locking leaves together - This combination eliminates the bottom flushbolt and eliminates floor preparation
  - 20 minute fire rating for wood doors up to 4 feet wide by 9 feet tall
  - U/M - Set Consists of 1 Top Flushbolt and 1 Bottom Fire Bolt
  - Fully automatic - Bolt retracts when active door is opened - Bolt extends when active door is closed
  - Non-handed
  - Consists of one 292S and one 293S for two point latching
  - Inactive door remains latched until the active door is opened, releasing the automatic bottom bolt - Top bolt can be manually released - Inactive door will relatch automatically when closed
  - Non-handed
  - Bolt head rods are adjustable

Automatic Flush Bolt Set with Fire Bolt  
For Wood Doors



**Product Specifications**

---

- Faceplate:** - 1" x 8-1/2" (25 mm x 216 mm)
- Flattened Square Bolt Head:** - 1/2" (13 mm)
- Bolt Throw:** - 3/4" (19 mm)
- Materials:** - Stainless steel and brass with steel components
- Finishes:** - US3, US4, US10, US10B, US15, US32, US32D
- Fasteners:** - Three (3) #10 x 1" SMS  
- Six (6) #8 x 1" combo screws  
- Two (2) plastic anchors
- Mortise Strike:** - 15/16" x 2-1/4" (24 mm x 57 mm)
- Bolt Backset:** - 3/4" (19 mm)
- Certifications:** - ANSI/BHMA 156.3 Type #25

