

3600 Series Lever

Grade 2 Tubular Lever

Applications:

- Heavy Duty Residential
- Medium Duty Commercial
- No exposed mounting screws
- Non-handed
- Conventional cylinder or Small Format Interchangeable Core housing available



PRODUCT SPECIFICATIONS

CERTIFICATIONS:

- BHMA Certified ANSI A156.2, Series 4000, Grade 2
- ADA Compliant ANSI A117.1 Accessibility Code
- UL/cUL Listed for all functions up to 3 hours for "A" label single doors
- UL10C Positive Pressure Rated
- UL10B Neutral Pressure Rated
- Five-year warranty

EXPOSED TRIM:

- Levers: Cast zinc
- Rose: Wrought brass

LOCK CHASSIS:

- Heavy gauge steel, zinc dichromated

KEYS:

- Two operating keys supplied per lock

ROSE DIAMETER:

- 2-15/16" (75 mm)

CYLINDERS/CORES:

- Brass 6-pin - Keyed Different - Schlage C Keyway - standard
- Cylinder drilled 6 pin, Keyed 5 pin - standard
- Other keying options, including keyed 6 pin, available from factory
- Zero bit cylinders will be 6 pin keyed - standard
- SFIC uncombined or combined, brass 6 pin or 7 pin cores sold separately

DOOR THICKNESS:

- 1-3/8" - 1-3/4" (35 mm - 45 mm)

BACKSET:

- Adjustable 2 3/8" - 2 3/4" (60 mm - 70 mm)
- Preset at factory for 2 3/8" (60 mm)

LATCHBOLT:

- 1/2" (13 mm) Throw - Stainless steel
- 1" x 2 1/4" (25 mm x 57 mm) Faceplate
- Deadlocking latchbolt prevents manipulation when door is closed; keyed functions only
- Square corner faceplate standard, round corner available

STRIKES:

- 3935 ASA 1-1/4" x 4-7/8" strike (32 mm x 124 mm) strike - Standard

FUNCTIONS:

- 10 - Passage, 17 - Dummy, 40 - Privacy, 53 - Entry, 70 - Classroom, 80 - Storeroom

FINISHES:

- US3, US4, US10, US10B, US26, US26D

OPTION:

- Tactile warning
- Split finish

STANDARD DOOR PREP:

- 2-1/8" (54 mm) diameter (cross bore)
- Latch hole: 1" diameter (edge bore)

LEVER OPTIONS:

- Archer, August, Withnell lever