

9890 Series and 9891 Series

Heavy Duty Aluminum
Box Track and Hardware



Notes:

- Top and bottom pivots are heavy duty with ball bearing bottom socket assembly for smooth, long lasting operation
- 9890 Series requires 1741 loose pin hinges -- included
- Quick release hanger allows easy door hanging and removal
- For doors 1-1/8" - 1-3/4" (29 mm - 44 mm) thick
- Up to 125 lbs (57 kg) per panel bi-fold
- Up to 75 lbs (34 kg) per panel multi-fold
- Track is extruded aluminum jump-proof style with "V" shaped rails
- Hangers have four 1-1/4" (32 mm) diameter wheels

PRODUCT SPECIFICATIONS

PACKAGED SETS:

9890 Series Set for two doors includes one 9801 track, two 9827 hanger, two 9828 pivot, and six 1741 3.5"x3.5" US2D hinges

- 9890-30: 30" (762 mm) opening for two doors
- 9890-36: 36" (914 mm) opening for two doors
- 9890-48: 48" (1219 mm) opening for two doors

9891 Series Set for four doors includes one 9801 track, two 9827 hangers, two 9828 pivots, and six 1741 3.5"x3.5" US2D hinges

- 9891-48: 48" (1219 mm) opening for four doors
- 9891-60: 60" (1524 mm) opening for four doors
- 9891-72: 72" (1829 mm) opening for four doors
- 9891-96: 96" (2438 mm) opening for four doors

TRACK LENGTH:

- 9801-72: 72" (1829 mm)
- 9801-96: 96" (2438 mm)
- 9801-120: 120" (3048 mm)
- 9801-144: 144" (3658 mm)
- 9801-192: 192" (4877 mm)

INSTALLATION:

- Clearance between door bottom and top of 9122 track must be 5/8" (16 mm) minimum to 1" (25.4 mm) maximum

PRODUCT SIZE OPTIONS

PART #	DESCRIPTION
9890-30	30" (762 mm) Opening 2 Doors
9890-36	36" (914 mm) Opening 2 Doors
9890-48	48" (1219 mm) Opening 2 Doors