



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

2978 Touchless Exit Switch

2978

Touchless Infrared Exit Switch with Illuminated Status Indication

Applications

Designed to control electric locks/strikes, magnetic locks, or automatic door operators

No touch wave-to-exit switch

Active with a wave of the hand

Ideal in cleanrooms, hospitals, labs, schools, or offices for sanitary exit applications

PRODUCT SPECIFICATIONS

Activation:

1 second or as long as sensor is triggered

Case Quantity:

12

Electrical Specifications:

30 mA standby; 70 mA Active @ 12VDC | 15 mA standby; 35 mA

Active @ 24VDC - Input power

SPDT, dry 3A @ 30VDC - Form C Relay 1

SPDT, dry 3A @ 30VDC - Form C Relay 2

Features:

Quick connect screwless terminal block for easy installation

Uses infrared sensor technology

4" max read range

No moving parts

Auto-sensing 12/24VDC voltage input

Output activation time: 1 second or as long as the sensor is triggered

LED Color:

Standby - red; Active - green

LED Indicators:

Red - Standby

Green - Active

Operating Temperature:

-4deg F ~ 131deg F (-20C ~ 55C)

Range:

4" (10 cm)

Size:

4-1/2" Height

2-3/4" Width

Warranty:

1 Year

