



PRODUCT SPECIFICATIONS  
For more information visit [www.hagerco.com](http://www.hagerco.com)

## 2925 - Electric Door Strike

2925

Electric Strike - Used with cylindrical locksets with up to 5/8" latch

### Applications

Designed for use with cylindrical and mortise lockset with up to 5/8" throw latch bolts with 1/8" door gap



### PRODUCT SPECIFICATIONS

#### Accessories:

- 2-679-0028 - Buzzer 12/24 VDC
- 2-679-0029 - Rectifier for AC operation

#### Case Quantity:

8

#### Electrical Specifications:

- 200/100 mA @ 12/24 VDC Solenoid
- 3A @ 30VDC Latch Monitoring (SPDT)

#### Faceplate:

4-7/8" (124 mm) faceplate for aluminum, wood, and hollow metal frames

#### Features:

- Quick and easy installation with compact low profile 1-1/4" backset
- Internally mounted solenoid and factory-supplied mounting tabs
- Fail Secure - Field reversible for fail-safe
- Non-Handed
- Latch status monitoring standard

#### Finishes:

US32D

#### Latch Status:

SPDT, 3 amp @ 30 VDC

#### Material:

All stainless steel parts with durable diecast body for corrosion resistance

#### Notes:

- The latch must enter at the strike "Centerline" located exactly between the top and bottom of the strike faceplate. Refer to strike installation instructions and template to determine strike location prior to frame preparation.
- Not to be installed in an inactive door leaf

#### Size:

- 4-7/8" H
- 1-1/4" W
- 1-1/4" D

#### Special Note 1:

Monitoring Latch Status (Std): SPDT, DRY 3A @ 30VDC

#### Warranty:

1-Year