



PRODUCT SPECIFICATIONS  
For more information visit [www.hagerco.com](http://www.hagerco.com)

## 2928 - Multi-Application Electric Strike

2928

Medium Duty Electric Strike used with single doors using a cylindrical or mortise lockset with up to a 3/4" latch bolt throw. (3/4" latch bolt throw requires a minimum 1/8" door gap)



### Applications

Grade 2 Medium-Duty Electric Strike

Used with single doors using a cylindrical or mortise lockset with up to a 3/4" latch bolt throw. (3/4" latch bolt throw requires a minimum 1/8" door gap)

### PRODUCT SPECIFICATIONS

#### Accessories:

- 2-679-0028 - Buzzer 12/24 VDC
- 2-679-0029 - Rectifier for AC operation

#### Case Quantity:

8

#### Certifications:

ANSI A156.31, Grade 2

#### Electrical Specifications:

- 200/100mA @ 12/24VDC - Solenoid | 140/70mA @ 12/24VAC - Solenoid
- SPDT, 3A @ 30VDC - Latch Monitoring
- SPDT, 3A @ 30VDC - Keeper Closed & Locked Status
- SPDT, 3A @ 30VDC - Keeper Open/Closed (Optional)

#### Faceplate:

Square and Radius options

#### Features:

- Quick and easy installation with low profile 1-3/16" backset
- Internally mounted solenoid and factory-supplied mounting tabs
- Non-handed
- Fail secure standard; field reversible to fail-safe
- Field selectable voltage - 12/24V, AC/DC
- Plug-in connectors
- Latch position status (standard)
- Keeper locked/unlocked status (standard)
- KOC - Keeper open/closed and status (optional)
- Fewer moving parts for maximum life
- 1/4" (6 mm) horizontal alignment adjustment

#### Finishes:

US32D (Square Corner), ALM (Radius Corner)

#### Material:

All stainless steel parts with durable diecast body for corrosion resistance. (Square corner faceplates, stainless steel. Radius corner faceplates, aluminum)

#### Notes:

- The latch must enter at the strike "Centerline" located exactly between the top and bottom of the strike faceplate. Refer to strike installation instructions and template to determine strike location prior to frame preparation.
- Additional finishes are available. Inquire with Hager Customer Service for pricing
- Not to be installed in an inactive door leaf

#### Size:

- 2928-SC - 1-1/4" W x 4-7/8" H x 1-3/16" D
- 2928-RC - 1-1/4" W x 4-7/8" H x 1-3/16" D

2928-6R - 1-1/4" W x 6-7/8" H x 1-3/16" D

2828-7R - 1-7/16" W x 7-15/16" H x 1-3/16" D

#### Warranty:

1 Year