



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

2916P Heavy Duty Keypad Outdoor - Prox

2916P

Heavy Duty Keypad Indoor/Outdoor with Prox
Reader



Applications

Surface mount indoor/outdoor keypad with Prox reader
Designed to control access of a single entry point for facilities
with up to 500 users
Each user can be assigned a personal identification number
(PIN) and/or Prox credential

PRODUCT SPECIFICATIONS

Accessories:

- 2-679-0021 - HID ProxCard II - 25 Cards
- 2-679-0022 - HID ProxCard II - 100 Cards
- 2-679-0023 - HID ProxCard II - 10 Fobs
- 2-679-0024 - HID ProxCard II - 100 Fobs

Case Quantity:

8

Electrical Specifications:

- 30mA typical, 150 mA maximum @ 12/24 VAC/VDC (Auto Sensing)
- Power Input
- Form "C", 5 amps @ 28VDC - Relay 1
- Form "C", 2 amps @ 28VDC - Relay 2
- Switch to common 100 mA @ 30VDC - Solid Status Output 3
- Switch to common 100 mA @ 30VDC - Solid Status Output 4

Features:

- 500 users, Card and/or 4-6 digit PIN codes
- Tactile audible keypress, select volume
- Keypad tamper lockout (number of attempts 2-7, lockout time 60 seconds)
- Request-to-exit/Enter input, egress keypad input
- Choice of door sense/relay inhibit input functions (forced entry, door ajar, inhibit relay 1 or 2, auto relock when the door closes)
- Choice of 2 solid status output functions (alarm shunt, forced entry, door ajar, tamper lockout, keypad active)
- Heavy cast metal blue backlit keys

Operating Temperature:

- 20° to 130°F (-30° to 54°C) - Operating Humidity: 5 - 95% (non-condensing)

Size:

- 5-3/4" Height
- 3" Width
- 1-7/16" Depth

Warranty:

- 1 Year