



PRODUCT SPECIFICATIONS  
For more information visit [www.hagerco.com](http://www.hagerco.com)

## 2953 - Single with 1200 lbs holding force

2953

1,200 lb. holding force, Surface mount - single, 12/24VDC

### Applications

For perimeter and interior door security and access control



### PRODUCT SPECIFICATIONS

Case Quantity:  
2

Warranty:  
1 Year

Certifications:  
ANSI/BHMA A156.23 Grade 1 Compliant

Electrical Specifications:  
125mA @ 12/24VDC - Power Input (Auto Sensing)  
SPDT, dry 250mA @ 30VDC - Anti-Tamper Switch (Optional)  
SPDT, dry 250mA @ 30VDC - Door Position Sensor (Optional)  
SPDT, dry 250mA @ 30VDC - Magnetic Bond Sensor (Optional)

Features:  
Can be ordered with optional features factory-installed or added as modular upgrade kits  
Field upgradeable without removal  
Quick mount assembly  
Compatible with any access control system  
Secure wiring and mounting screws with interlocking mounting plate

Finishes:  
ALM or DBZ

Module Options:  
2-679-0109 - Timer Input Field installed upgrade  
2-679-0110 - Door Position Switch Field installed upgrade  
2-679-0111 - Magnetic Bond Sensor Field installed upgrade  
2-679-0112 - Anti-Tamper Switch Field installed upgrade

Mounting Kits:  
Top Jamb Kit  
Glass Door Kit  
Universal Header Bracket  
Spacer Bracket  
Armature Mounting Plate with and without Sensor  
Door Coordinator Lock Mounting Kit  
Filler Plates  
Angle Brackets  
See "2950 Accessory Reference List" in related files for a complete list of all mounting kits and part numbers

Options:  
Timer Input (Time) - Built-in field adjustments 0-30 seconds re-lock delay  
Door Position Switch (DPS) - Indicates door open and door closed  
Anti-Tamper Switch (ATS) - Indicates access cover removal  
Magnetic Bond Sensor (MBS) - Indicates locked and unlocked, low holding power, tampering, and obstruction between the armature and magnetic core

Product Name:  
Single magnetic lock with 1200 lbs. holding force

Size:  
11" (l) x 2-3/4" (h) x 1-9/16" (d)