



PRODUCT SPECIFICATIONS
For more information visit www.hagerco.com

2954 - Double with 1200 lbs holding force each

2954

1,200 lb. holding force, Surface mount - double,
12/24VDC



Applications

For perimeter and interior door security and access control

PRODUCT SPECIFICATIONS

Case Quantity:
2

Warranty:
1 Year

Certifications:
ANSI/BHMA A156.23 Grade 1 Compliant

Electrical Specifications:
250mA @ 12/24VDC - Power Input (Auto Sensing)
SPDT, dry 250mA @ 30VDC - Anti-Tamper Switch (Optional)
SPDT, dry 250mA @ 30VDC - Door Position Sensor (Optional)
SPDT, dry 250mA @ 30VDC - Magnetic Bond Sensor (Optional)

Features:
Can be ordered with optional features factory-installed or added as modular upgrade kits
Field upgradeable without removal
Quick mount assembly
Compatible with any access control system
Secure wiring and mounting screws with interlocking mounting plate

Finishes:
ALM or DBZ

Module Options:
2-679-0109 - Timer Input Field installed upgrade
2-679-0110 - Door Position Switch Field installed upgrade
2-679-0111 - Magnetic Bond Sensor Field installed upgrade
2-679-0112 - Anti-Tamper Switch Field installed upgrade

Mounting Kits:
Top Jamb Kit
Glass Door Kit
Universal Header Bracket
Spacer Bracket
Armature Mounting Plate with and without Sensor
Door Coordinator Lock Mounting Kit
Filler Plates
Angle Brackets
See "2950 Accessory Reference List" in related files for a complete list of all mounting kits and part numbers

Options:
Timer Input (Time) - Built-in field adjustments 0-30 seconds re-lock delay
Door Position Switch (DPS) - Indicates door open and door closed
Anti-Tamper Switch (ATS) - Indicates access cover removal
Magnetic Bond Sensor (MBS) - Indicates locked and unlocked, low holding power, tampering, and obstruction between the armature and magnetic core

Product Name:
Double magnetic lock with 1200 lbs. holding force

Size:
22" (l) x 2-3/4" (h) x 1-9/16" (d)