



PRODUCT SPECIFICATIONS
For more information visit www.hagerco.com

4801 - Non-Latching Push Bar

4801

Applications

Heavy duty pressure release bar suitable for high traffic openings

Used for magnetic lock release, access control request-to-exit, delayed egress trigger, alarm shunt, CCTV activation or alarm activation

Narrow, low profile minimizes projection for an aesthetically superior design



PRODUCT SPECIFICATIONS

Activation Force:

Factory set at 5 lbs. (2.2 kg)

Field adjustable up to 15 lbs. (6.8 kg)

Case Quantity:

6

Door Width:

36" Standard, Optional 42" & 48" available

Electrical Specifications:

20 mA @ rest, 115 mA active @ 12/24 VDC (auto sensing) - Power

Input

SPDT Dry, 3A @ 28 VDC - Relay 1

SPDT Dry, 3A @ 28 VDC - Relay 2

Features:

Human touch not required allows the bar to be activated while wearing gloves

"PUSH TO EXIT" sign - 1" green letters supplied (Field installed)

10' cable with 18" flexible stainless steel armored power loop

No moving parts, limits wear and tear while providing quick and quiet operation

Activation Force: 5 lbs. (2.2 kg) Field adjustable up to 15 lbs. (6.8 kg)

Tri-Failsafe - provides an additional switch in case the two sensors fail

Finishes:

Aluminum (ALM)

Black (BLK)

Operating Temperature:

0° to 150° F (-18° to 66° C)

Product Name:

Non-Latching Push Bar

Size:

2-3/8" Height

1-7/8" Depth

Warranty:

One-year

H Width:

2-3/8"