




PRODUCT SPECIFICATIONS
For more information visit www.hagerco.com

2-659-0240 - Programmable Relay & Door Sequencer

2-659-0240

Programmable relay for door timing and advanced relay sequencing



Applications

Capable of simple and advanced relay logic this product provides a single solution for a variety of applications
Used with automatic doors, access control, automation, and single-occupancy restrooms

PRODUCT SPECIFICATIONS

Box Quantity:
1

Case Quantity:
20

Electrical Specifications:

Supply Voltage: 12 to 24 V AC/DC
Power Consumption: 30 to 130 mA
Relay #1(Dry): 3 A @24 VAC / 30 VDC
Relay#1(Wet): 1 A @ 5-24 VAC/VDC
Relay #2: 3 A @24 VAC / 30 VDC
Relay #3: 1 A @24 VAC / 30 VDC

Features:

Intuitive programming
Three integrated relays; two 3 AMP and one 1 AMP
Built-in surge suppression eliminates the need for external components when installing electric locking devices
Relay hold times up to 60 seconds per relay
Delay times between relay; 1/4, 1/2, and 3/4 second options

Functions:

10 - Simple Timer
11 - Ratchet/Latching
22 - 2 relay Sequence Inhibitor with Door Position Input
28 - 2 Relay Sequence with Door Position Input
29 - Relay 1 Deactivation Timer
36 - 3-Relay Sequencer + "1-shot"
37 - 3-Relay Sequencer with "Independent Relay"
50 - Interlock Timer with Door Position Inputs
55 - Interlock Ratchet with Door Position Inputs
65 - 2-Way, 2 Relay Sequence
nL - Normally Locked Restroom
nU - Normally Unlocked Restroom
dn - 3-Relay Sequencer + "Day/Night Mode"
00 - Disable (default)

Material:

Housing Material: Clear ABS Plastic

Operating Temperature:

-15 degrees to 150 degrees F

Size:

1.0" (Height)
5.2" (Width)
2.2" (Depth)

Warranty:

1 Year