



## PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

# 500-048

Concealed Leaf With Sheet Metal fasteners 1-1/6"  
Nominal Leaf Thickness

## Applications

Bearings spaced to distribute door weight evenly up to 50 lbs  
Can be used for vertical or horizontal applications  
Alignment ribs for easy installation and proper hinge location



## PRODUCT SPECIFICATIONS

Clearance:  
5/16" (8 mm)

Fasteners:  
Standard: #8-18 x 3/4" Truss Head Phillips Tapping AB Zinc plated  
Steel  
For sheet metal or wood applications

Features:  
Universal hinge used for a wide variety of applications including marine applications, wood cabinet construction, medical equipment, portable exhibits and displays, electronic cabinets, switchboxes, etc.  
Bearings spaced to distribute door weight evenly up to 50 lbs.  
Can be used for vertical or horizontal applications  
Alignment ribs for easy installation and proper hinge location

H Length:  
24", 36", 48", 72"

Length Options:  
Standard and Custom

Material:  
Aluminum 6063-T6

Notes:  
1/16" (1.5 mm) leaf thickness, EPD: Roton Continuous Hinges  
Environmental Product Declaration

Warranty:  
All Roton products have a lifetime warranty. When ordering electric Roton, the electric portion of the hinge has a one-year warranty.