



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

790-903

Half Surface, 1/8" Inset, Door of Any Material

Applications



PRODUCT SPECIFICATIONS

Certifications:

ANSI A156.26 Grade 1 for 150-pound doors, UL

Clearance:

1/8" minimum hinge side plus standard lockside clearance

Door Reinforcement:

Wood - None required up to 200 lbs. For metal doors, a 1/8" (3 mm) thick reinforcement plate is recommended along the hinge edge for proper thread engagement of the adjustment studs.

Electric Modifications:

Power Transfer Preparation (EPT 2) or (EPT 10)

Fastener Size:

#10-24 x 5/8" S/S Drill-Kwik® (metal frame), #1/4-20 x 3/4" 2C Drill-Kwik® (metal door), #1/4-14 x 1" 2C Type AB (wood door)

Fire Rating:

Up to 3 hr. metal and 90 min. wood composite

Frame Reinforcement:

None required to 200 lbs. Heavier weight use 16-gauge channel.

H Length:

79", 83", 85", 95", 119"

Length Options:

Standard and Custom

Material:

14 Ga. (0.075") Type 304 Stainless Steel

Maximum Door Length:

10'-0"

Maximum Door Thickness:

1-3/4"

Maximum Door Weight:

300 lbs

Notes:

Any nonstandard length hinge may require a custom hole pattern based on the requested length. Consult Hager Companies to address the field prep for the doors and frames.

Optional Features:

Sheared leaf, Raised Barrel (SWAGED), Wide Throw, Security Studs, Dutch Door Prep (DUTCH), Powder Coat

Options:

Optional sex bolts available (specify when ordering)

Special Features:

1/4" (6.3 mm) diameter Stainless Steel Pin. Dual 6/6 Nylon bearings between each knuckle. Security molding, 1/8" (3.2 mm) inset.