



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

5D

Round Wrought Door Pull

Applications



PRODUCT SPECIFICATIONS

Box Quantity:
1

Case Quantity:
12

Category:
Pulls

Certifications:
EPD
Meets ANSI A156.6 for J401 Pulls

Clearance:
1- 1/2"

Door Thickness:
1-3/4" (45 mm)

Fasteners:
Two 1/4" - 20 thru bolts with finish washers

Fastener Size:
1/4" -20 x 2-1/4"

Finishes:
US3, US4, US10, US10B, DBZ, US26, US26D, US28, US32,
US32D

Handicap:
2- 1/2" (64 mm) clearance available on special orders. Add prefix
"H" to number (i.e. H5D)

Material:
Aluminum, Brass, Bronze, Stainless Steel

Notes:
If ordered with tempered glass, specify glass thickness and hole
size
Not suitable for back to back mounting

Optional Features:
May be combined with a plate to make a pull plate. 2-1/2" (64mm)
Clearance available on special orders. Add prefix "H" to number
(i.e. H5D)

Projection:
2-1/8" (54 mm)

Pull Clearance:
1-1/2" (38 mm)

Pull CTC:
5-1/2" (140 mm)

Pull Diameter:
5/8" (16 mm)