



## PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

# 282D

## Manual Flush Bolt for Metal Doors

### Applications



## PRODUCT SPECIFICATIONS

### Bolt:

Backset: 3/4" (19 mm)

### Bolt Throw:

3/4" (19 mm)

### Box Quantity:

2

### Case Quantity:

80

### Category:

Flush Bolts & Coordinating Devices

### Certifications:

Three-hour fire rating for metal doors up to 4' wide by 10' tall  
Meets ANSI 156.16 for L04251

### Faceplate:

1" x 6-3/4" (25 mm x 171 mm)

### Fasteners:

Eight #8 x 3/4" combo screws, Eight #8 x 1-1/2" combo screws

### Finishes:

US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26,  
US26D

### Guide Plate Height:

2" (51 mm)

### Guide Plate Width:

1" (25 mm)

### Material:

Brass faceplate with steel components

### Mortise Strike Length:

2-1/4" (24 mm x 57 mm)

### Mortise Strike Width:

15/16" (24 mm)

### Notes:

Sold and priced in increments of two  
282S strike plate bag and 282P bolt head available  
For use on hollow metal/fire rated doors  
Non-handed  
Bolt heads are adjustable  
Bolt head, if required, may be ordered as part 282P

### Optional Features:

Rod Length: 18" (457 mm), 25" (635 mm), 30" (762 mm)- Specify  
282R

### Rod Length:

12" (305 mm) from center of face to corner of door