



## PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

# 291D

## Automatic Flush Bolt Set for Wood Covered Composite Doors

### Applications



## PRODUCT SPECIFICATIONS

### Bolt:

Bolt Backset: 3/4" (19 mm)

### Bolt Throw:

3/4" (19 mm)

### Box Quantity:

2

### Case Quantity:

40

### Category:

Flush Bolts & Coordinating Devices

### Certifications:

1-1/2 hour fire rating on wood doors up to 4' wide by 9' tall (B, C, D, and E label rating)  
Meets ANSI 156.3 Type #25

### Faceplate:

2" x 8-1/2" (45 mm x 216 mm)

### Fasteners:

Three #10 x 1" SMS, Six #8 x 1" combo screws, Two plastic anchors

### Finishes:

US3, US4, US10, US10B, US15, US32, US32D

### Flattened Round Bolt Head:

1/2" (13 mm)

### Material:

Stainless steel/brass with steel components

### Mortise Strike Length:

2-1/4" (57 mm)

### Mortise Strike Width:

15/16" (24 mm)

### Notes:

Thermal lock automatically locks inactive door under high fire/heat conditions  
280X dust proof strike are recommended for use with these sets  
Used in pairs at top and bottom of inactive door  
Fully automatic - bolts retract when active door is opened; bolts extend when active door is closed  
Non-handed  
Bolt head rods are adjustable.