



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

295W

Automatic Flush Bolt with Fire Bolt for Wood Doors

Applications



PRODUCT SPECIFICATIONS

Bolt Throw:
3/4" (19 mm)

Box Quantity:
1

Case Quantity:
10

Category:
Flush Bolts & Coordinating Devices

Certifications:
20 minute fire rating for wood doors up to 4" wide x 9" tall. ANSI
A156.3 Type #25

Faceplate:
1" x 8-1/2" (25 mm x 216 mm)

Fasteners:
Three #10 x 1" SMS, Six #8 x 1" combo screws, Two plastic
anchors

Finishes:
US3, US4, US10, US10B, US15, US32, US23D

Flattened Round Bolt Head:
Square bolt head 1/2" (13 mm)

Material:
Stainless steel and brass with steel components

Mortise Strike Height:
2-1/4" (57 mm)

Mortise Strike Width:
15/16" (24 mm)

Notes:
Fire bolt is activated at 230° F projecting into active door locking
leaves together
This combination eliminates the bottom flush bolt and eliminates
floor preparation
U/M Set consist of one top flush bolt and one bottom fire bolt
Fully automatic - bolt retracts when active door is opened
Bolt extends when active door is closed
Consists of one 292S and one 293S for two point latching
Inactive door remains latched until the active door is opened,
releasing the automatic bottom bolt
Top bolt can be manually released
Inactive door will re-latch automatically when closed
Non-handed
Bolt heads are adjustable