



PRODUCT SPECIFICATIONS
For more information visit www.hagerco.com

292D

Automatic Flush Bolt Set for Metal Doors

Applications



PRODUCT SPECIFICATIONS

Bolt:

Backset: 3/4" (19 mm)

Bolt Throw:

3/4" (19 mm)

Box Quantity:

1

Case Quantity:

10

Category:

Flush Bolts & Coordinating Devices

Certifications:

3-hour fire rating on metal doors up to 4' wide x 9' tall (A, B, C, D, and E label rating)
Meets ANSI 156.3 Type #25

Faceplate:

2" x 6-3/4" (27 mm x 172 mm)

Fasteners:

Ten #8 x 1" combination screws

Finishes:

US3, US4, US10, US10B, US15, US32, US32D

Flattened Round Bolt Head:

1/2" (13 mm)

Material:

Stainless steel and brass with steel components

Mortise Strike Length:

2-1/4" (57 mm)

Mortise Strike Width:

15/16" (24 mm)

Notes:

Thermal lock automatically locks inactive door under high fire/heat conditions
280X dust proof strike are recommended for use with these sets
Used in pairs at top and bottom of inactive door
Fully automatic- bolts retract when active door is opened; bolts extend when active door is closed
Non-handed
Bolt head rods are adjustable