



PRODUCT SPECIFICATIONS
For more information visit www.hagerco.com

293D

Constant Latching Flush Bolt Set for Inactive Metal Doors

Applications



PRODUCT SPECIFICATIONS

Bolt:

Backset: 3/4" (19 mm)

Bolt Throw:

3/4" (19 mm)

Box Quantity:

1

Case Quantity:

10

Category:

Flush Bolts & Coordinating Devices

Certifications:

3 hour fire rating on metal doors up to 4' wide x 9' tall (A, B, C, D, and E label rating)
ANSI A156.3 Type #27

Faceplate:

1" x 6-3/4" (25 mm x 172 mm)

Fasteners:

Eight #8 x 1" combination screws

Finishes:

US3, US4, US10, US10B, US15, US32, US32D

Flattened Round Bolt Head:

Square bolt head 1/2" (13 mm)

Material:

Stainless steel and brass with steel components

Notes:

Thermal lock automatically locks inactive door under high fire/heat conditions
280X dust proof strike are recommended for use with these sets
3-hour fire rating for metal doors up to 4 feet wide x 9 feet tall
Consists of one 292S and one 293S for two point latching
Inactive door remains latched until active door is opened, releasing the automatic bottom bolt
Top bolt can be manually released by pressing plunger
Inactive door will re-latch automatically when closed
Non-handed
Bolt head rods are adjustable

T-Strike:

1-1/8" x 2-3/4" (28 mm x 70 mm)