



PRODUCT SPECIFICATIONS  
For more information visit [www.hagerco.com](http://www.hagerco.com)

## 294D

Constant Latching Flush Bolt Set for Wood Doors

### Applications



### PRODUCT SPECIFICATIONS

**Bolt:**

Backset: 3/4" (19 mm)

**Bolt Throw:**

3/4" (19 mm)

**Box Quantity:**

1

**Case Quantity:**

10

**Category:**

Flush Bolts & Coordinating Devices

**Certifications:**

1-1/2 hour fire rating for wood doors up to 4' wide x 9' tall (B, C, D, and E label rating)  
ANSI A156.3 Type #27

**Faceplate:**

1" x 8-1/2" (25 mm x 216 mm)

**Fasteners:**

Three #10 x 1" SMS, Four #8 x 1" combo screws, Two plastic anchors

**Finishes:**

US3, US4, US10, US10B, US15, US32, US32D

**Flattened Round Bolt Head:**

Square bolt head 1/2" (13 mm)

**Material:**

Stainless steel and brass with steel components

**Notes:**

One set consist of one 291S and one 294S for two point latching  
Thermal lock automatically locks inactive door under high fire/heat conditions  
280X dust proof strikes are recommended for use with these sets  
Inactive door remains latched until the active door is opened, releasing the automatic bottom bolt  
Top bolt can be manually released. Inactive door will re-latch automatically when closed  
Non-handed  
Bolt head rods are adjustable

**T-Strike:**

1-1/8" x 2-3/4" (28 mm x 70 mm)