



PRODUCT SPECIFICATIONS
For more information visit www.hagerco.com

295M

Automatic Flush Bolt with Fire Bolt for Metal Doors

Applications



PRODUCT SPECIFICATIONS

Bolt:

Backset: 3/4" (19 mm)

Bolt Throw:

3/4" (19 mm)

Box Quantity:

1

Case Quantity:

10

Category:

Flush Bolts & Coordinating Devices

Certifications:

3-hour fire rating for metal doors up to 4' wide x 9' tall. ANSI A156.3
Type #25

Faceplate:

1" x 6-3/4" (25 mm x 172 mm)

Fasteners:

Ten #8 x 1" combination screws

Finishes:

US3, US4, US10, US10B, US15, US19, US32, US32D

Flattened Round Bolt Head:

Square bolt head 1/2" (13 mm)

Material:

Stainless steel and brass with steel components

Mortise Lock Width:

15/16" (24 mm)

Mortise Strike Length:

2-1/4" (57 mm)

Notes:

Fire bolt is activated at 230° F projecting into active door locking
leaves together

This combination eliminates the bottom flushbolt and eliminates
floor preparation

U/M Set consist of one top flushbolt and one bottom fire bolt

Fully automatic- bolt retracts when active door is opened

Bolt extends when active door is closed

Non-handed

Bolt heads are adjustable