



PRODUCT SPECIFICATIONS
For more information visit www.hagerco.com

3353 - Entry

Applications

Multi-Family
Residential



PRODUCT SPECIFICATIONS

Backsets:

Adjustable 2-3/8" - 2-3/4" (60mm - 70mm)

Certifications:

Meets BHMA A156.2 Grade 3 test standards

Cylinders/Cores:

Keyed Different - standard
Cylinder drilled 5 pin - Only
Other Keying options done by others

Door Thickness:

1-3/8" - 1-3/4" (35 mm - 45 mm)

Exposed Trim:

Wrought Brass Rose
Cast Zinc Levers

Finishes:

US3, US10B, US15, US26 and US26D
Finishes other than US26D will be subject to extended lead times

Functions:

Entry

Keyway:

Schlage C - Only

Latchbolt Type:

1/2" (13 mm) throw, zinc1" x 2-1/4" (25 mm x 57 mm) faceplate
Deadlocking latchbolt prevents manipulation when door is closed
4-Way Latch (Square corner and Round corner faceplate provided)

Lever Options:

Archer, August, Johnston and Withnell

Notes:

Box Packed
Turn button locking on interior side

Rose Diameter:

2-9/16" (65mm)

Standard Door Prep:

Cylinder hole: 2-1/8" (54 mm) diameter (cross bore)
Latch hole: 1" (25 mm) diameter (edge bore)

Strikes:

Round corner full-lip strikes - standard
Square coner full lip and Tee Strike available separately

Warranty:

One-year