



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

3833S - Classroom (E06091)

Applications

Heavy Duty Commercial
Industrial
Institutional



PRODUCT SPECIFICATIONS

Backsets:

2-3/4" (70mm)

Cylinders/Cores:

Brass - keyed different - Schlage C keyway - standard
Drilled 6-Pin, Keyed 5-Pin - standard
Other keying options, including keyed 6-pin, available from factory
Zero bit cylinders will be 6 pin keyed - standard
SFIC mortise housings available
SFIC uncombined or combined, brass 6- or 7-pin cores sold separately - standard
LFIC mortise housings available
LFIC zero bitted or combined, brass 6-pin sold separately – standard. Schlage C keyway only.
Schlage "L" cam is used standard on Hager mortise locks

Deadbolt:

1" (25 mm) throw - stainless steel

Door Thickness:

1-3/4" - 2" (45 mm - 51 mm)

Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep

Finishes:

US3, US4, US10B, US26 and US26D

US3, US4 and US26 subject to extended lead time

Functions:

Classroom (E06091)

Handing:

Required

Keyway:

Schlage C - Standard, other keyways optional

Lock Chassis:

4-5/16" x 3-9/16" x 1" (110 mm x 90 mm x 25 mm)

Notes:

Self adjusting case for beveled doors

Strikes:

1-1/8" x 3-1/2" (29 mm x 89 mm) no-lip

Warranty:

Lifetime