




## PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

# 3836S - Single Cylinder

## Applications

Heavy Duty Commercial  
Industrial  
Institutional



## PRODUCT SPECIFICATIONS

### Backsets:

2-3/4" (70mm)

### Certifications:

ADA Compliant ANSI A117.1 Accessibility Code

### Cylinders/Cores:

Brass - keyed different - Schlage C keyway - standard  
Drilled 6-Pin, Keyed 5-Pin - standard  
Other keying options, including keyed 6-pin, available from factory  
Zero bit cylinders will be 6 pin keyed - standard  
SFIC mortise housings available  
SFIC uncombined or combined, brass 6- or 7-pin cores sold separately - standard  
LFIC mortise housings available  
LFIC zero bitted or combined, brass 6-pin sold separately – standard. Schlage C keyway only.  
Schlage "L" cam is used standard on Hager mortise locks

### Deadbolt:

1" (25 mm) throw - stainless steel

### Door Thickness:

1-3/4" - 2-1/2" (45 mm - 64 mm)

Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep

### Functions:

Single Cylinder

### Keyway:

Schlage C - Standard

### Lock Chassis:

4-5/16" x 3-9/16" x 1" (110 mm x 90 mm x 25 mm)

### Notes:

Self adjusting case for beveled doors

### Strikes:

1-1/8" x 3-1/2" (29 mm x 89 mm) no-lip strike standard

### Warranty:

Lifetime