



## PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

# 3863S - Classroom (F29)

## Applications

Heavy Duty Commercial  
Industrial  
Institutional



## PRODUCT SPECIFICATIONS

### Backsets:

2-3/4" (70mm)

### Cylinders/Cores:

Brass - keyed different - Schlage C keyway - standard  
Drilled 6-Pin, Keyed 5-Pin - standard  
Other keying options, including keyed 6-pin, available from factory  
Zero bit cylinders will be 6 pin keyed - standard  
SFIC mortise housings available  
SFIC uncombined or combined, brass 6- or 7-pin cores sold separately - standard  
LFIC mortise housings available  
LFIC zero bitted or combined, brass 6-pin sold separately – standard. Schlage C keyway only.  
Schlage "L" cam is used standard on Hager mortise locks

### Deadbolt:

1" (25 mm) throw - stainless steel

### Door Thickness:

1-3/4" - 2" (45 mm - 51 mm)

Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep

### Finishes:

US3, US4, US10B, US26 and US26D

US3, US4 and US26 subject to extended lead time

### Functions:

Classroom (F29)

### Handing:

Required

### Keyway:

Schlage C - Standard, other keyways optional

### Lock Chassis:

4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)

### Notes:

Self adjusting case for beveled doors

### Strikes:

1-1/4" x 4-7/8" (32 mm x 124 mm) no-lip strike - standard

### Warranty:

Lifetime