



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

9890-30

Bi-fold set for two 15" doors

Applications



PRODUCT SPECIFICATIONS

Case Quantity:
6

Clearance:
Clearance between door bottom and top of 9122 track must be
5/8" (16 mm) minimum to 1" (25.4 mm) maximum

Door Thickness:
For doors 1-1/8" - 1-3/4" (29 mm - 44 mm) thick

Installation:
Clearance between door bottom and top of 9122 track must be
5/8" (16 mm) minimum to 1" (25.4 mm) maximum

Maximum Door Thickness:
1-3/4" (44 mm)

Maximum Door Weight:
Up to 125 lbs (57 kg) per panel bi-fold,
Up to 75 lbs (34 kg) per panel multi-fold

Notes:
Top and bottom pivots are heavy duty with ball bearing bottom
socket assembly for smooth, long lasting operation

9890 Series requires 1741 loose pin hinges -- included

Quick release hanger allows easy door hanging and removal

Track is extruded aluminum jump-proof style with "V" shaped rails

Hangers have four 1-1/4" (32 mm) diameter wheels

Packaged Sets:
9890 Series Set for two doors includes one 9801 track, two 9827
hanger, two 9828 pivot, and six 1741 3.5"x3.5" US2D hinges
9890-30: 30" (762 mm) opening for two doors