



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

9630CS

For 3'0" wide x 7'0" high doors up to 150 lbs (68 kg) per door.

Applications



PRODUCT SPECIFICATIONS

Case Quantity:

1

Certifications:

Meets performance requirements for ANSI/BHMA 156.14 (Grade 1)
f

Type: D02311-150
ADA Compliant

Door Specifications:

For doors 1-3/8" - 1-3/4" (35mm - 44 mm) thick, up to 3'0" (914 mm) wide and 7'0" (2184 mm), For door weighing up to 150 lbs (68 kg)

Door Thickness:

For doors 1-3/8" - 1-3/4" (35mm - 44 mm) thick

Installation:

For Bi-Parting Doors use Hager Double Pocket Door Kit 9639 (sold separately), Joins 2 pocket door frames to make one large doorway. Rough opening width changes to 4 times one door width.

Maximum Door Weight:

150 lbs (68 kg)

Notes:

For size options review the Size Options Chart

For kit contents see Related Files

Options:

Soft Close mechanism (1-269-8651) is available, sold separately.
(Use of Soft Close mechanism exceeds ADA 5 lb. of opening force threshold)
See Related Files for additional information.

Specifications:

Pre-assembled header assembly goes up quickly
Easy door installation and removal for painting and repair
2 pair of wood split studs with wood inserts • size 3/4" (19 mm) x 1-5/8" (26 mm) length relative to height • steel encased for rigidity and to prevent fastener penetration into the pocket
Track header unit attaches to rough framing at both ends
Split studs can be nailed or screwed to track header