



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

9631CS

For 3'0" wide x 6'8" high doors up to 150 lbs (68 kg) per door.

Applications



PRODUCT SPECIFICATIONS

Case Quantity:

1

Certifications:

Meets performance requirements of ANSI/BHMA 156.14 (Grade 1) f

Type: D02311-250

ADA Compliant

Conforms To:

ANSI A156.14/ Type: D8671, D8701

Door Specifications:

Up to 3'0" (914 mm) wide and 6'8" (2032 mm) high

Door Thickness:

For doors 1-3/8" - 1-3/4" (35mm - 44 mm) thick

Installation:

For Bi-Parting Doors use Hager Double Pocket Door Kit 9639 (sold separately)

Joins 2 pocket door frames to make one large doorway. Rough opening width changes to 4 times one door width

Maximum Door Thickness:

1-3/4" (44 mm)

Notes:

For size options review the Size Options chart, For kit contents see Related Files

Options:

Soft Close mechanism (1-269-8651) is available, sold separately. (Use of Soft Close mechanism exceeds ADA 5 lb. of opening force threshold)

See Related Files for additional information.

Specifications:

Heavy-Duty, V-groove, jump-proof aluminum track

Pre-assembled header assembly goes up quickly

Easy door installation and removal for painting and repair, 2 pair of wood split studs with wood inserts • size 3/4" (19 mm) x 1-5/8" (26 mm) length relative to height

Steel encased for rigidity and to prevent fastener penetration into the pocket

Track header unit attaches to rough framing at both ends

Split studs can be nailed or screwed to track header