



## PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

# 9628CS

## Applications



## PRODUCT SPECIFICATIONS

### Case Quantity:

1

### Certifications:

ADA Compliant

### Conforms To:

ANSI A156.14 (Grade 1), Type: D02311-150

### Door Specifications:

Up to 3'0" (914 mm) wide and 9'0" (2743mm)

### Door Thickness:

For doors 1-3/8" - 1-3/4" (35mm - 44mm) thick

### Installation:

For Bi-Parting Doors use Hager Double Pocket Door Kit 9639 (sold separately)

Joins 2 pocket door frames to make one large doorway. Rough opening width changes to 4 times one door width. See Related Files for additional information.

### Maximum Door Weight:

150 lbs (68 kg)

### Notes:

For kit contents see Installation Instructions

### Options:

Soft Close mechanism (1-269-8651) is available, sold separately. See Related Files for additional information. (Use of Soft Close mechanism exceeds ADA 5 lb. of opening force threshold)

### Specifications:

V-groove jump-proof aluminum track

Pre-assembled header assembly goes up quickly

Easy door installation and removal for painting and repair 3/4" (19 mm) x 1-3/4" (44 mm)

Split Studs Split Studs are steel encased wood for rigidity and to prevent fastener penetration into the pocket

Header assembly attaches to rough-in framing at both ends

Split studs can be nailed or screwed to the Header Assembly