




PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

9850HD

For 4'0" wide x 8'0" high doors, up to 250 lbs.(113 kg) per door.

Applications



PRODUCT SPECIFICATIONS

Case Quantity:

1

Certifications:

Meets performance requirements of ANSI/BHMA 156.14 (Grade 1) for sliding doors by exceeding 100,000 cycles in operation.

Type: D02311-250

ADA Compliant

Door Specifications:

Up to 4'0" (1219 mm) wide and 8'0" (2438 mm) high

Door Thickness:

For doors 1-3/8" - 1-3/4" (35 mm - 44 mm) thick

Installation:

For Bi-Parting Doors use Hager Double Pocket Door Kit 9639 (sold separately,

Joins 2 pocket door frames to make one large doorway. Rough opening width changes to 4 times one door width

Maximum Door Weight:

250 lbs. (113 kg)

Options:

Soft Close mechanism (1-269-8651) is available, sold separately.

See Related Files for additional information.

Available in 102" (2591 mm) at an extended lead time. Please contact Hager customer service for additional details.

Specifications:

Heavy-Duty, V-groove, jump-proof aluminum track, Pre-assembled header assembly goes up quickly, Easy door installation and removal for painting and repair, 3 pair of wood split studs with wood inserts • size 3/4" (19 mm) x 1-5/8" (26 mm) length relative to height

- steel encased for rigidity and to prevent fastener penetration into the pocket Track header unit attaches to rough framing at both ends, Split studs can be nailed or screwed to track header

Website Note:

For size options review the Size Options chart

For kit contents see Related Files

Compares to:

- Stanley PDF250
- Lawrence PF619