



## PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

# 313S

## Applications



## PRODUCT SPECIFICATIONS

### Certifications:

Meets ANSI A156.6 for J401 pull and ANSI A156.6 for J407 pull plate

### Clearance:

1-5/8" (41mm)

### Door Thickness:

1-3/4" - 2" (45mm - 51mm)

### Finishes:

US32D

### Functions:

Dummy

### Hardware Requirements:

-Dummy - four 1/4" - 20 x 3/4" FPHMS and four finish washers -  
Mortise lock - four 1/4" - 20 x 3/4" FPHMS and four finish washers -  
Exit device - supplied with exit device

### H Height:

11" (279mm)

### Material:

11 GA stainless steel

### Notes:

For use with most mortise locks on out-swinging doors  
For use with many exit devices. Thru bolts directly to device.  
Must order cylinders separately  
When mounting trim to a Hager exit device, retaining cup (2-649-0137) must be purchased to ensure proper installation and a 7/16" (11 mm) tall cylinder collar must be purchased when using a 1-1/4" to 1-3/8" (32mm - 35mm) long rim cylinder (See instructions for more detail)

### Options:

Cylinder cutout available [1-1/4" (32mm) diameter standard for exit device use and 1-1/2" (38mm) diameter standard for mortise lock use]

### Projection:

1-7/8" (478mm)

### Pull Clearance:

1-5/8" (41mm)

### Size:

6-11/32" x 11" (161mm x 280mm)