



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

4900U

Applications

For use with 4500, 4600, and 4700 Series rim exit devices on fire rated pairs of doors



PRODUCT SPECIFICATIONS

Available Sizes:

- 84" (2134 mm)
- 96" (2438 mm)
- 120" (3048 mm)

Certifications:

- Panic rated

Fasteners:

- Four (4) each 5/16" - 18 x 5/8" (16 mm) FHPMS (top bracket)
- Two (2) each 5/16" - 18 x 1-1/2" (38 mm) FHPMS (top bracket)
- Four (4) each 5/16" - 18 x 1-1/2" (38 mm) FHMS (bottom bracket)
- Four (4) each 5/16" - 18 masonry anchors
- Two (2) each 1/4" - 20 x 1-1/4" FHPMS (top fitting)
- Two (2) each 1/4" - 20 thru bolts (top fitting)
- Two (2) #10 - 24 x 3/8" - 20 x 1-1/4" FHPMS (top fitting)

Finishes:

- USP - grey primer only

Material:

- 11 gauge steel tube

Mullion:

- 2" x 3" (51 mm x 76 mm) - 11 gauge steel tube

Notes:

- Shim kits supplied standard

Shims:

- Two (2) each 1/2" (13 mm) and 5/8" (16 mm) spacers included (top). Two (2) 1/16" (1.6 mm) shims included (bottom).

Strikes:

- Panic rated mullions use standard rim strike supplied with exit device

Warranty:

- One-year