



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

7000 Series Heavy Duty Concealed Mount

Heavy Duty Concealed Mount

Applications

- 7015C- Concealed friction
- 7016C- Concealed stop only
- 7017C- Concealed hold open

PRODUCT SPECIFICATIONS

Box Quantity:
1

Case Quantity:
6

Certifications:

- BHMA and ANSI 156.8 Compliant
- UL/cUL Listed for up to 3 hours (stop only)
- UL10C Positive Pressure Rated (stop only)
- UL10B Neutral Pressure Rated (stop only)

Door Thickness:

- 1-3/4" (44 mm) thick door - standard
- 1-3/8" - 2-1/4" (36 mm - 57 mm) thick door - optional

Fasteners:

Standard screw packet included for wood or metal door and frame applications

Finishes:

- US10B
- US32D (for stainless steel)
- ALM

Handing:

Non-handed

Material:

Steel, stainless steel

Mounting Style:

Concealed

Notes:

- Adjustable arms provide easy installation
- Slide track design
- Adjustable in the field
- Heavy shock absorber spring provides 5° to 7° compression before dead stop
- Special templating upon request
- Single and double acting doors
- Degree of opening is fully adjustable and can be adapted to changing needs between 85° to 110°

Size:

- Size 1 (SZ1) = 24"- 40" door
- Size 2 (SZ2) = 41"- 55" door

Warranty:

Five years

