PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com



29EA - Door Prop Alarm

Applications

Exit alarm on door opening with audible sirens and adjustable timer







PRODUCT SPECIFICATIONS

Box Quantity:

1

Electrical Specifications:

60mA @ 12/24VDC - Input Power Form C, 2A @ 30VDC (Resistive) - Alarm Ouput (Main) Form C, 2A @ 30VDC (Resistive) - Alarm Ouput (Auxiliary) Trigger Input (DPS): N/O or N/C Dry Contact (Field selectable) Reset/Bypass Input (Control): N/O or N/C Dry Contact (Field selectable)

Features:

85dB Piezo buzzer alarm Vandal-resistant aluminum construction with security screws Bypass status indicator light Automatic or manual alarm reset Output relays for remote monitoring Optional key switch or mortise cylinder key switch

Functions:

N - No Key Switch M - Mortise Cylinder Switch (sold separately) K - Key Switch

LED Indicators:

Integral bi-color LED status indicator Green - normal operation Red - alarm activated

Notes:

Mounting depth of 2-1/8" recommended Door status sensor (DPS) sold separately Trigger input sold separately (Commonly request to exit switch from electrified hardware or PIR sensor)

Product Name:

Door Prop Alarm

Size

29EA-N - 5"h x 3.25"w x 1.625" d 29EA-M - 5"h x 5"w x 1.875"d 29EA-K - 5"h x 5"w x 1.875"d

Warranty:

One-year