



PRODUCT SPECIFICATIONS
For more information visit www.hagerco.com

2-659-0336 Single Housing with Primary and Secondary Modules - Superscan Active Infrared Safety Sensor Door Mounted

2-659-0336

Safety Sensor Door Mounted (single with slave
model)



Applications

Mounts to the door to provide protection for pedestrian
automatic doors

Ideal for hospitals, warehouses, and assisted living facilities to
protect doors and pedestrians

PRODUCT SPECIFICATIONS

Activation:

Detect the presence of a pedestrian (up to 8'), while the door is
opening and closing using triangulation

Box Quantity:

1

Case Quantity:

6

Detection Range:

0" - 96" (0'-8')

Detection Time:

< 50 ms

Electrical Specifications:

Max 60mA @ 2/24 VAC/VDC - Power Input

1A @ 30V (resistive) - Output

12-24 VDC - Inhibit input (inhibited when voltage is applied)

Features:

Detect the presence of a pedestrian (up to 8'), while the door is
opening and closing using triangulation

Each module detection zone can be adjusted independently

Functions:

Detection mode - NO or NC

Normal mode

Background analysis mode

H Height:

1.9"

LED Indicators:

Master: Red LED = Detection | Green LED = Active Output

Slave: Red LED = Detection

H Length:

34.5"

Maximum Mounting Height:

96" (8')

Mounting Style:

Top of Door

Operating Temperature:

-30°F - 140°F

Power Requirements:

12-24 VAC/VDC

Product Name:

Superscan Active Infrared Safety Sensor

H Technology:

Active infrared

Warranty:

1 Year

H Width:

1.95"