




PRODUCT SPECIFICATIONS  
For more information visit [www.hagerco.com](http://www.hagerco.com)

# 451 Double Lipped Strike - Center Hung Doors

451

Center Hung Double Lipped Strike

## Applications



## PRODUCT SPECIFICATIONS

Box Quantity:  
1

Certifications:  
ANSI A1882

Door Thickness:  
1-3/4"

Fastener Size - Machine:  
1/2" x 8-32"

Finishes:  
US26D

Gauge:  
See Sizing Chart Options

H Height:  
See Sizing Chart Options

Hole Count:

Material:  
Brass

Notes:  
Center hung doors. To be used with Hager 600, 611, and 612 pivots and door release - this allows doors to be opened in both directions without damage to frame. Standard latchbolt cutout is 1-1/4" x 11/16" (32 mm x 17 mm). Standard strike plates are optimized for cylindrical locks/latches mounted on 1-3/4" thick doors. Mortise lock applications require special latch cutout location (consult specific manufactures for variations of cutout dimensions). For use with Camtrol double acting pivot. Frame width: 5-3/4" x 2-3/4"

Options:  
Other sizes available, contact Hager Customer Service.

Product Name:  
Double Lipped Strike for Center Hung Doors

H Width:  
See Sizing Chart Options